



### MODEL OVERVIEW:

**SUMMARY:** *The V-710DM is designed to provide the flexibility of automating "jumbo" format gripper arm inserters and ink jet / tabber bases using one friction feeder. By simply repositioning the sheet-detect photo-eye mounted on a flexible arm extension, the V-710DM allows for quick and easy installation onto most major brands of vacuum / non-vacuum bases and gripper arm inserters.*

**APPLICATIONS:**

- Gripper arm inserters • Ink jet bases
- Labeling bases • Tabber bases

**INCREASE PRODUCTIVITY / MAXIMIZE R.O.I.**



### THINK AUTOMATION

One friction feeder that works on your addressing base and gripper arm inserter? With the V-710DM this kind of flexibility is now available. The impressive flexibility of the V-710DM was not achieved at the expense of performance. Greater throughput is assured with reliable feeding up to 10,000 pieces per hour on your inserter and up to 25,000 #10 envelopes per hour on your addressing base.

Streamfeeder Universal Feeding Solutions™ are designed to be flexible and innovative solutions to even the most challenging applications, providing fast payback through increased efficiency and ease of use.

### STANDARD FEATURES

- Patented Differential Friction Technology™ for reliable product separation.
- 24-inch (60.96cm) hopper with easy two-knob adjustment.
- Tool-free adjustments for easy setups and changeovers.
- Variable angle feed belts enhance feeding performance.
- Variable speed control for synchronous operation.
- Durable lightweight construction.
- Integrated lifting handle simplifies moving and installation.

### SPECIFICATIONS

Maximum Product Size:	12 ¼ in. W x 14 in. L (31.12 cm x 35.56 cm)
Minimum Product Size:	3 ¾ in. W x 3 ¾ in. L (9.53 cm x 9.53 cm)
Optional:	2 ½ in. W x 2 ½ in. L (6.35 cm x 6.35 cm)
Product Thickness:	.002 in. to .750 in. (.005 cm to 1.91 cm)
Optional:	.002 in. x 1 in. (.005 cm to 2.54 cm)
Productivity (#10 envelopes):	Up to 10,000 pph (inserter) Up to 25,000 pph (ink jet)
Power Input:	115/230vac 50/60Hz – 3A
Controls:	AC diffuse reflective product sensor Variable speed control Dynamic brake
Construction:	Powder coated Cold rolled hinged steel enclosure
Overall Dimensions:	14 7/8 in. W (37.54 cm) 18 1/8 in. L (47.22 cm) 26 1/2 in. H (67.39 cm)
Warranty:	Two-year limited (90-days motor)

