

SPECIFICATION

Strapping speed	2.5 sec/strap (60Hz)
Tension	30 - 90 lbs.
Sealing method	heating element
Strap width	6, 9, 12, 15.5mm of P.P band 1/4", 3/8", 1/2", 5/8"
Reel outside Dia.	19"
Power	AC 110/220, 50/60Hz, 1 PH
Power consumption	0.57KW
Table height	30 inches
Machine weight	220 lbs.
Layout dimension	29½"H x 36¼"W x 23"D
Identification	H-height, W-width, D-depth

*Specification subject to change without notice.

SCOPE OF APPLICATION: GENERAL PURPOSE INDUSTRIAL STRAPPING

FEATURE

- CE safety standard design
- Safety switch
- Reliable P.C. Board electric control
- Hinge type table
- Rigid caster with brake
- Reel unit is core size adjustable design for 8", 9" & 11" diameter.



PC-101

SPECIFICATION

Strapping speed	2.5 sec/strap (60Hz)
Tension	30 - 90 lbs.
Sealing method	heating element
Strap width	6, 9, 12, 15.5mm of P.P band 1/4", 3/8", 1/2", 5/8"
Reel outside Dia.	19"
Power	AC 110/220, 50/60Hz, 1 PH
Power consumption	0.57KW
Table height	30 inches
Machine weight	185 lbs.
Layout dimension	29½"H x 36¼"W x 23"D
Identification	H-height, W-width, D-depth

*Specification subject to change without notice.

**SCOPE OF APPLICATION:
GENERAL PURPOSE
INDUSTRIAL STRAPPING****FEATURE**

- CE safety standard design
- Safety switch
- Reliable P.C. Board electric control
- Hinge type table
- Rigid caster with brake
- Reel unit is core size adjustable design for 8", 9" & 11" diameter.

**PC-102**