


RELIANT 1500

Universal Friction Feeder®



Streamfeeder
®

RELIANT 1500

Universal Friction Feeder®



Whatever the inserter on your production floor – Phillipsburg, Inscerco, Kern, or another similar type – with a compact Reliant 1500 aboard you'll operate at a new level of productivity and profitability.

Experience ultra-flexible performance that begins with patented Differential Friction Technology™. This superior feeding method precisely separates,

singulates and presents virtually any type and size of material to your inserter's gripper jaw.

Efficiently designed for maximum operator productivity, job setups and changeovers are easily and quickly accomplished with the turn of a knob. A large, 24-inch (60.96 cm) capacity hopper is conveniently loaded from the front or back. The brushless and clutch-free motor provides dependable feeding performance up to 10,000 pieces per hour.

The rugged Reliant 1500 is built to last with quality precision components. Design and construction have proven so superior that it carries a two-year limited warranty.

STANDARD FEATURES

- Ideal for Phillipsburg, Inscerco, Kern, and similar type inserters
- Patented Differential Friction Technology™ provides exact sheet separation and singulation
- Compact 10-inch (25.40 cm) width allows side-by-side mounting
- Feeds up to 10,000 pieces per hour
- Brushless and clutch-free high speed motor for dependable, trouble-free operation
- Handles most insert types, sizes, and thicknesses
- Single knob adjustment makes setup fast and easy
- 24-inch (60.96 cm) capacity hopper is easily loaded from front or back of feeder
- Sealed precision bearings never require lubrication

OPTIONS

- Selectivity interface for inserters with on-board intelligence

SPECIFICATIONS

Maximum Insert Size:	9 in. W x 8 1/2 in. L (22.86 cm x 21.59 cm)
Minimum Insert Size:	1 1/4 in. x 2 1/4 in. L (4.13 cm x 6.35 cm)
Thickness Range:	.002 in. to .250 in. (.05 mm to 6.35 mm)
Insert Types:	Z-folds, gatefolds, payment booklets, coated and slick stacks, overwrapped products, and standard products when greater capacity is needed
Speed:	10,000 pieces per hour
Hopper Capacity:	24 in. (60.96 cm)
Drive:	AC synchronous motor
Power Input:	115V/230V 50/60 Hz
Current:	1 amp
Sensor:	Diffuse reflective
Switch:	Power On/Off
Enclosure:	Powder coated cold rolled steel
Overall Dimensions:	11 1/2 in. L (28.89 cm) 10 in. W (25.40 cm) 25 1/2 in. H (63.82 cm)
Weight:	Approx. 23 lb. (10.41 kg)
Warranty:	Two-year limited warranty



Your Authorized Streamfeeder Reseller is:

MAILERS ENGINEERING, INC.
1647 Blake Avenue
LOS ANGELES, CALIFORNIA 90031
(323) 343-9750 FAX (323) 343-9753



103 Osborne Road
Minneapolis, Minnesota 55432-3120 USA
TEL: 612.502.0000
FAX: 612.502.0100
E-MAIL: info@streamfeeder.com
WEB: www.streamfeeder.com